



GALACTIC 11 UFO SELECT
SPECIFICATION SHEET
ECO-11EHB

Galactic 11 UFO Select LED High Bay Light I

ECO-11EHB 11
120-277 V



KEY SPECS

POWER	COLOR	EFFICACY	OPTICS
150–240_W Field-selectable output	3_{CCT} 4000 / 5000 / 5700 K	160_{lm/W} System efficacy	120° Beam angle

Galactic 11 UFO Select delivers field-selectable wattage and CCT output from a heavy die-cast aluminum housing in black or white, paired with a high-transparency PC lens and Lumileds SMD 2835 LEDs for uniform 120° coverage. A universal 120–277 V driver provides 0–10V dimming with an optional plug-and-play occupancy sensor, and the fixture suspends from a unique hook for fast install in warehouses, manufacturing, and big-box retail. UL, cUL, and DLC listed for utility rebate eligibility, backed by EcoLite's 10-year non-prorated warranty.

FEATURES

- 01 Field-selectable 150 / 200 / 240 W
- 02 Field-selectable 4000 / 5000 / 5700 K
- 03 160 lm/W efficacy with Lumileds SMD 2835
- 04 Die-cast aluminum housing, black or white
- 05 0–10V dimming standard
- 06 Plug-and-play occupancy sensor optional

Warehouse &
distribution centers

Manufacturing facilities

Convention centers &
sporting arenas

Cold storage facilities



01

ORDER INFORMATION

SKU / MODEL	WATTAGE	CCT	VOLTAGE
ECO-11EHB-150/200/240W-4000/5000/5700K-120V	150/200/240 W	4000/5000/5700 K	120-277 V
ECO-11EHB-150W-120V-50K	150 W	5000 K	120-277 V

02

ELECTRICAL CHARACTERISTICS


SPECIFICATION	150/200/240 W	150 W
Wattage	150 / 200 / 240 W	
Color Temperature (CCT)	4000 / 5000 / 5700 K	4000K / 5000K / 5700K
Efficacy (lm/W)	160 lm/W	
Input Voltage	120-277 V AC	
Lumen Output	24,000 / 32,000 / 38,400 lm	
Operating Temperature	-36 to +60°C	
CRI	>80	
LED Driver	UL-listed, 0-10V dimmable	UL-listed, 0-10V dimmable
Beam Angle	120°	
Certifications	UL, cUL, DLC	
HID Equivalent	200-750 W MH/HPS	200-250 / 250-600 / 600-750 W MH/HPS
Junction Temperature	<75°C	
Lamp Efficiency	≥90%	
Warranty	10 Year Non-Prorated	

03

ACCESSORIES & MOUNTING



EMERGENCY
BATTERY BACKUP 30W
ECO-EMUFO-30347-YYY



EMERGENCY DRIVER 40W
ECO-LSA40FY-170



EMERGENCY DRIVER 25W
ECO-LSUFO-25170-YYII



EMERGENCY DRIVER 40W
ECO-LSUFO-40170-YYII



ALUMINUM
REFLECTOR 150W 90°
ECO-150W UFO REFLECTOR



ALUMINUM
REFLECTOR 200W 90°
ECO-200W UFO REFLECTOR



MOTION SENSOR
ECO-ANT-5



MOTION SENSOR
ECO-ANT-6



BLUETOOTH PIR
SENSOR 12VDC
ECO-HB04DPR-A



PIR SENSOR
ECO-HD07VR-PH-2



REMOTE CONTROLLER
ECO-Remote controller

04

DIMENSIONS

MODEL	DIAMETER	HEIGHT
ECO-11EHB-150/200/240W-4000/5000/5700K-120V	12.2" / 310 mm	7.2" / 183 mm
ECO-11EHB-150W-120V-50K	12.2" / 310 mm	7.2" / 183 mm

Round footprint · Dimensions ±0.2" · inches [mm]

05

SAFETY WARNING

⚠ READ BEFORE INSTALLATION

- 1
- Installation must be performed by a qualified, licensed electrician in accordance with all applicable national and local electrical codes.