EcoLite™
Leader in LED Lighting

GALACTIC 11 UFO SELECT
SPECIFICATION SHEET
ECO-LS-11EHB

# Galactic 11 UFO Select LED High Bay Light I

**ECO-LS-11EHB** 11
120–277 V



## KEY SPECS

| POWER | COLOR | EFFICACY | OPTICS |
|---|---|---|---|
| 150–240W | 3CCT | 160lm/W | 120° |
| Field-selectable output | 4000 / 5000 / 5700 K | System efficacy | Beam angle |

**Galactic 11 UFO Select** delivers field-selectable wattage and CCT output from a heavy die-cast aluminum housing in black or white, paired with a high-transparency PC lens and Lumileds SMD 2835 LEDs for uniform 120° coverage. A universal 120–277 V driver provides 0–10V dimming with an optional plug-and-play occupancy sensor, and the fixture suspends from a unique hook for fast install in warehouses, manufacturing, and big-box retail. UL, cUL, and DLC listed for utility rebate eligibility, backed by EcoLite's 10-year non-prorated warranty.

- Warehouse & distribution centers
- Manufacturing facilities
- Convention centers & sporting arenas
- Cold storage facilities

## FEATURES

01 Field-selectable 150 / 200 / 240 W
02 Field-selectable 4000 / 5000 / 5700 K
03 160 lm/W efficacy with Lumileds SMD 2835
04 Die-cast aluminum housing, black or white
05 0–10V dimming standard
06 Plug-and-play occupancy sensor optional

c UL us LISTED · DLC LISTED · 10 Year Non-Prorated WARRANTY

POWER SELECT
MULTI-WATTAGE

COLOR SELECT
FIELD SELECTABLE

160+ LM/W
HIGH EFFICACY

## 01 ORDER INFORMATION

| SKU / MODEL | WATTAGE | CCT | VOLTAGE |
|---|---|---|---|
| ECO-LS-11EHB-150/200/240W-4000/5000/5700K-120V | 150/200/240 W | 4000/5000/5700 K | 120–277 V |
| ECO-LS-11EHB-150W-120V-50K | 150 W | 5000 K | 120–277 V |

## 02 ELECTRICAL CHARACTERISTICS


| SPECIFICATION | 150/200/240 W | 150 W |
|---|---|---|
| Wattage | 150 / 200 / 240 W | |
| Color Temperature (CCT) | 4000 / 5000 / 5700 K | 4000K / 5000K / 5700K |
| Efficacy (lm/W) | 160 lm/W | |
| Input Voltage | 120–277 V AC | |
| Lumen Output | 24,000 / 32,000 / 38,400 lm | |
| Operating Temperature | -36 to +60°C | |
| CRI | >80 | |
| LED Driver | UL-listed, 0–10V dimmable | UL-listed, 0-10V dimmable |
| Beam Angle | 120° | |
| Certifications | UL, cUL, DLC | |
| HID Equivalent | 200–750 W MH/HPS | 200–250 / 250–600 / 600–750 W MH/HPS |
| Junction Temperature | <75°C | |
| Lamp Efficiency | ≥90% | |
| Warranty | 10 Year Non-Prorated | |

## 03 ACCESSORIES & MOUNTING



**EMERGENCY BATTERY BACKUP 30W**

ECO-LS-EMUFO-30347-YYY



**EMERGENCY DRIVER 40W**

ECO-LSA40FY-170



**EMERGENCY DRIVER 25W**

ECO-LSUFO-25170-YYII



**EMERGENCY DRIVER 40W**

ECO-LSUFO-40170-YYII



**ALUMINUM REFLECTOR 150W 90°**

ECO-LS-150W-UFO-REFLECTOR



**ALUMINUM REFLECTOR 200W 90°**

ECO-LS-200W-UFO-REFLECTOR



**MOTION SENSOR**

ECO-LS-ANT-5



**MOTION SENSOR**

ECO-LS-ANT-6



**BLUETOOTH PIR SENSOR 12VDC**

ECO-LS-HB04DPR-A



**PIR SENSOR**

ECO-LS-HD07VR-PH-2



**REMOTE CONTROLLER**

ECO-LS-REMOTE-CONTROLLER

## 04 DIMENSIONS

| MODEL | DIAMETER | HEIGHT |
|---|---|---|
| ECO-LS-11EHB-150/200/240W-4000/5000/5700K-120V | 12.2" / 310 mm | 7.2" / 183 mm |
| ECO-LS-11EHB-150W-120V-50K | 12.2" / 310 mm | 7.2" / 183 mm |

Round footprint · Dimensions ±0.2" · inches [mm]

## 05 SAFETY WARNING

**⚠ READ BEFORE INSTALLATION**

1. Installation must be performed by a qualified, licensed electrician in accordance with all applicable national and local electrical codes.