EcoLite™
Leader in LED Lighting

VECTOR FULL SELECT SLIM WALL PACK
SPECIFICATION SHEET
ECO-LS-3FWP

Vector Full Select Slim Wall Pack LED Light I

ECO-LS-3FWP
120-277



KEY SPECS

POWER	COLOR	EFFICACY	OPTICS
60–120W	3CCT	160lm/W	III
Field-selectable output	3000 / 4000 / 5000 K	System efficacy	NEMA distribution

Vector Full Select Slim Wall Pack delivers full-cutoff exterior illumination from a heavy die-cast aluminum housing with a bronze powder-coated finish and a UV-resistant polycarbonate refractor lens. High-output LEDs drive a Type III distribution at >80 CRI with field-selectable wattage and CCT. A universal 120–277 V driver provides 0-10V dimming, and an integrated photocell enables dusk-to-dawn control. Wall-mounted installation is straightforward, the fixture is IP65 wet-location rated, and it ships UL/cUL-listed and DLC Premium qualified for utility rebates, backed by EcoLite's 10-year non-prorated warranty.

FEATURES

01 Field-selectable 60 / 90 / 100 / 120 W
02 Field-selectable 3000 / 4000 / 5000 K CCT
03 160 lm/W efficacy with >80 CRI
04 Built-in photocell with 0-10V dimming
05 Die-cast aluminum housing, bronze finish
06 Type III full-cutoff distribution

- Warehouses & logistics centers
- Factory & industrial exteriors
- Shopping malls & supermarkets
- Building perimeter & wall-mounted security

c UL us LISTED
DLC LISTED PREMIUM
10 Year Non-Prorated WARRANTY
POWER SELECT MULTI-WATTAGE
COLOR SELECT FIELD SELECTABLE
IP65 INGRESS PROTECTED

01 ORDER INFORMATION

SKU / MODEL	WATTAGE	CCT	VOLTAGE
ECO-LS-3FWP-60/90/100/120W-XXK-U	60/90/100/120 W	3000/4000/5000 K	120-277

02 ELECTRICAL CHARACTERISTICS

SPECIFICATION	60/90/100/120 W
LED Driver	UL-listed Daermay brand, 0-10V dimmable
Wattage	60 / 90 / 100 / 120 W
Lumen Output	9,600 / 14,400 / 16,000 / 19,200 lm
Efficacy (lm/W)	160 lm/W
CRI	>80
Color Temperature (CCT)	3000 / 4000 / 5000 K
Input Voltage	120–277 V AC
Beam Angle	Type III, full cutoff
Operating Temperature	-30 to +45°C
Junction Temperature	<75°C
Lamp Efficiency	≥90%
Certifications	UL, cUL, DLC Premium
HID Equivalent	100–400 W MH/HPS

03 ACCESSORIES & MOUNTING



EMERGENCY BATTERY BACKUP 18W

ECO-LS-EMWC18W

04 DIMENSIONS

MODEL	LENGTH	WIDTH	HEIGHT
ECO-LS-3FWP-60/90/100/120W-XXK-U	14.48” / 368 mm	13.19” / 335 mm	6.44” / 164 mm

Rectangular footprint · Dimensions ±0.2” · inches [mm]

05 SAFETY WARNING

⚠ READ BEFORE INSTALLATION

1. Installation must be performed by a qualified, licensed electrician in accordance with all applicable national and local electrical codes.