



ALTAIR UP/DOWN PENDANT
SPECIFICATION SHEET
ECO-LS-4FT50W-35/40/50K

Altair Up/Down Pendant LED Linear Light I

ECO-LS-4FT50W-
35/40/50K
both



KEY SPECS

POWER	COLOR	EFFICACY	OPTICS
50W Rated output	3CCT 3500 / 4000 / 5000 K	115lm/W System efficacy	110° Beam angle

Altair Up/Down Pendant delivers tunable up/down architectural illumination with five field-selectable distribution ratios and independent CCT control for each lighting direction. The slim extruded aluminum housing carries a unique end cap for seamless continuous runs, and the universal 120–277 V driver supports 0-10V dimming. Available in 2 ft, 4 ft, and 8 ft lengths with pendant, surface, recessed, and wall mounting, the fixture suits commercial and hospitality interiors. Sensor and emergency-backup options are available, backed by EcoLite's 10-year non-prorated warranty.

FEATURES

- 01 Field-selectable up/down distribution (5 ratios)
- 02 Independent CCT control for uplight and downlight
- 03 Selectable 3500K / 4000K / 5000K
- 04 Seamless screwless end-cap connection
- 05 Pendant, surface, recessed, and wall mounting
- 06 0-10V dimming

Commercial & office spaces

Convention centers & lobbies

Hospitality & hotels

Showrooms



01 ORDER INFORMATION

SKU / MODEL	SIZE	WATTAGE	CCT	VOLTAGE
ECO-LS-4FT50W-35/40/50K	4 ft	50 W	3500/4000/5000 K	both

02 ELECTRICAL CHARACTERISTICS


SPECIFICATION	50 W
Size	4 ft
Wattage	50 W
Lumen Output	5,750 lm
Efficacy (lm/W)	115 lm/W
Color Temperature (CCT)	3500 / 4000 / 5000 K (selectable)
CRI	80+
Beam Angle	110°
Input Voltage	120-277 V
Dimming	0-10V

03 ACCESSORIES & MOUNTING



CANOPY MOUNT
WITH 6FT CABLE

ECO-4FT50W-Ceiling Mounting




LINKABLE CONNECTOR KIT

ECO-4FT50W-Linkable Kit




L-SHAPE CONNECTOR WHITE

ECO-L-Shape Connector



L-SHAPE CONNECTOR BLACK

ECO-L-Shape Linear



LINKABLE KIT

ECO-Linkable Kit




FLANGED RECESSED
MOUNT KIT

ECO-SCX2-FMRK-4FT



T-SHAPE CONNECTOR

ECO-T-Shape Connector




T-SHAPE CONNECTOR

ECO-T-Shape Linear



X-SHAPE CONNECTOR

ECO-X-Shape Connector



X-SHAPE CONNECTOR

ECO-X-Shape Linear

04 DIMENSIONS

MODEL	LENGTH	WIDTH	HEIGHT
ECO-LS-4FT50W-35/40/50K	48" / 1219 mm	2.63" / 67 mm	2.99" / 76 mm

Linear extrusion · Dimensions ±0.2" · inches [mm]

05 SAFETY WARNING

⚠ READ BEFORE INSTALLATION

- 1

Installation must be performed by a qualified, licensed electrician in accordance with all applicable national and local electrical codes.