EcoLite™
Leader in LED Lighting

EQUINOX EXIT FLOOD COMBO G
SPECIFICATION SHEET
ECO-LS-ES007SG

Equinox Exit Flood Combo G LED Exit Sign Light I

ECO-LS-ES007SG
120-277



KEY SPECS

POWER

5W

Rated output

Equinox Exit Flood Combo G delivers code-compliant emergency egress signage with a slim thermoplastic housing and a bright LED-illuminated EXIT face available in red or green letters. A 5 W universal 120/277 V input drives 12 high-output LEDs, while an integrated 3.6 V 800 mAh sealed lead-acid battery provides over 90 minutes of emergency operation and fully recharges within 24 hours. Field-selectable directional arrows and ceiling, wall, or back mounting support virtually any installation. Backed by EcoLite's 10-year non-prorated warranty.

- Commercial & office buildings
- Retail & hospitality spaces
- Schools & institutional facilities
- Healthcare & assisted-living facilities

FEATURES

01 Red or green LED EXIT face options
02 Universal 120/277 V input
03 Integrated sealed lead-acid battery backup
04 Over 90-minute emergency runtime
05 Field-selectable directional arrows
06 Ceiling, wall, or back mount installation



UNIVERSAL 120/277V
BATTERY BACKUP >90 MIN
RECHARGE 24 HR

01 ORDER INFORMATION

SKU / MODEL	WATTAGE	CCT	VOLTAGE
ECO-LS-ES007SG	5 W	—	120-277

02 ELECTRICAL CHARACTERISTICS

SPECIFICATION	5 W
Letter Color	Red (12 LEDs)
Wattage	5 W
Input Current	0.04 A
Input Voltage	120 / 277 V AC
Power Factor	0.86 PF
Output Wattage	1–2 W
Battery	Sealed lead-acid, 3.6 V / 800 mAh
Recharge Time	24 hr
Emergency Duration	>90 min
Product Size	430 × 187 × 45 mm

03 DIMENSIONS

MODEL	LENGTH	WIDTH	HEIGHT
ECO-LS-ES007SG	16.93” / 430 mm	7.36” / 187 mm	1.77” / 45 mm

Rectangular footprint · Dimensions ±0.2” · inches [mm]

04 SAFETY WARNING

⚠ READ BEFORE INSTALLATION

1. Installation must be performed by a qualified, licensed electrician in accordance with all applicable national and local electrical codes.