EcoLite™
Leader in LED Lighting

EQUINOX EXIT SIGN
SPECIFICATION SHEET
ECO-LS-ES037RG

Equinox Exit Sign LED Light I

ECO-LS-ES037RG
120-277



KEY SPECS

Equinox Exit Sign is a low-profile red/green LED exit sign engineered for code-compliant egress lighting in commercial and institutional spaces. The injection-molded housing carries a high-contrast acrylic panel with field-selectable red or green LED illumination, driven by an energy-efficient 1.5 W input circuit. A sealed 1.2 V / 800 mAh lead-acid battery delivers more than 90 minutes of emergency runtime and recharges within 24 hours. Universal 120/277 VAC input supports wall, ceiling, and end-mount installation. Backed by EcoLite's 10-year non-prorated warranty.

Commercial & retail buildings

Offices & institutional facilities

Schools & healthcare facilities

Hospitality & multifamily corridors

FEATURES

01 Field-selectable red or green LED panel

02 Universal 120/277 VAC input

03 1.2 V / 800 mAh sealed lead-acid battery backup

04 Over 90 minutes of emergency runtime

05 24-hour battery recharge time

06 Wall, ceiling, and end-mount installation

10 Year Non-Prorated WARRANTY

UNIVERSAL
120-277V

BATTERY BACKUP
>90 MIN RUNTIME

DUAL COLOR
RED OR GREEN

01 ORDER INFORMATION

SKU / MODEL	SIZE	WATTAGE	CCT	VOLTAGE
ECO-LS-ES037RG	11.73 × 7.36 × 1.77 in	1.5 W	—	120-277

02 ELECTRICAL CHARACTERISTICS

SPECIFICATION	1.5 W
Input Voltage	120–277 VAC
Wattage	1.5 W
Input Current	0.1 A
Output Wattage	1 W
Power Factor	0.86 PF
Battery	1.2 V / 800 mAh sealed lead-acid
Recharge Time	24 hr
Emergency Duration	>90 min
LED Source	SMD 2835
Product Size	11.73 × 7.36 × 1.77 in

03 DIMENSIONS

MODEL	LENGTH	WIDTH	HEIGHT
ECO-LS-ES037RG	11.73” / 298 mm	7.36” / 187 mm	1.77” / 45 mm

Rectangular footprint · Dimensions ±0.2” · inches [mm]

04 SAFETY WARNING

⚠ READ BEFORE INSTALLATION

1. Installation must be performed by a qualified, licensed electrician in accordance with all applicable national and local electrical codes.