EcoLite™
Leader in LED Lighting

URSA MAJOR EXIT SELECT
SPECIFICATION SHEET
ECO-LS-GLD037R

Ursa Major Exit Select LED Exit Sign Light I

ECO-LS-GLD037R
120-277



KEY SPECS

POWER

2W

Rated output

Ursa Major Exit Select delivers code-compliant emergency egress marking in a low-profile edge-lit panel with a uniformly illuminated red 8-inch legend and 1-inch stroke meeting UL 924 and New York City requirements for 100 ft viewing distance. The aluminum housing carries a sealed Ni-Cd battery providing over 120 minutes of emergency runtime with a 24-hour full recharge. It accepts a universal AC 120–347 V input, mounts to wall, ceiling, or end positions via knockouts and a universal spider plate, and ships with mounting hardware included. Backed by EcoLite's 10-year non-prorated warranty.

- Commercial & office buildings
- Retail & hospitality
- Schools & institutional facilities
- Healthcare facilities

FEATURES

01 Edge-lit red LED legend with uniform illumination

02 8-inch letter height with 1-inch stroke (UL 924, NYC approved)

03 Universal AC 120–347 V input

04 Ni-Cd 3.6 V / 600 mAh battery, >120 min emergency runtime

05 24-hour full recharge time

06 Wall, ceiling, or end mounting via universal spider plate

ENERGY STAR

UNIVERSAL
120-347V AC

BATTERY BACKUP
>120 MIN

01 ORDER INFORMATION

SKU / MODEL	SIZE	WATTAGE	CCT	VOLTAGE
ECO-LS-GLD037R	13.7 × 10.47 × 1.81 in	2 W	—	120-277

02 ELECTRICAL CHARACTERISTICS

SPECIFICATION	2 W
Input Voltage	120–347 V AC, 50/60 Hz
Wattage	4 W
Input Current	0.06 A
Power Factor	>0.9
Output Wattage	1 W
Battery	Ni-Cd 3.6 V / 600 mAh
Recharge Time	24 hr
Emergency Duration	>120 min
LED Source	8× red LED
Product Size	13.7 × 10.47 × 1.81 in

03 DIMENSIONS

MODEL	LENGTH	WIDTH	HEIGHT
ECO-LS-GLD037R	13.7” / 348 mm	10.47” / 266 mm	1.81” / 46 mm

Rectangular footprint · Dimensions ±0.2” · inches [mm]

04 SAFETY WARNING

⚠ READ BEFORE INSTALLATION

1. Installation must be performed by a qualified, licensed electrician in accordance with all applicable national and local electrical codes.