NOVA SELECT MAGNETIC STRIP KIT
SPECIFICATION SHEET
ECO-X-MTA

Nova Select Magnetic Strip Kit LED Area Lights II

ECO-X-MTA
120-277



KEY SPECS

POWER	COLOR	EFFICACY	VOLTAGE
18–60W	3CCT	Up to 131lm/W	120-277V
Field-selectable output	3000 / 4000 / 5000 K	System efficacy	Input voltage

Nova Select Magnetic Strip Kit delivers a versatile retrofit solution for existing linear fluorescent fixtures, built with a lightweight polycarbonate housing and a white diffuser that eliminates hotspots for even illumination. Field-selectable wattage and CCT let one SKU cover multiple applications, while a 0–10V dimmable driver and 120–277 V universal input simplify integration. Magnetic surface mounting allows quick installation in commercial, industrial, and educational interiors. cETLus listed for damp locations and DLC qualified, backed by EcoLite's 10-year non-prorated warranty.

- Commercial & office lighting
- Industrial & warehouse retrofit
- Educational facilities
- Fluorescent strip replacement

FEATURES

01 Field-selectable wattage and CCT (3000K / 4000K / 5000K)

02 0–10V dimmable driver, 100% to off

03 Universal 120–277 V AC input

04 Lightweight polycarbonate housing with white diffuser

05 CRI >80 with up to 131 lm/W efficacy

06 Magnetic surface-mount retrofit installation

Intertek · DLC LISTED · 10 Year Non-Prorated Warranty

POWER SELECT
MULTI-WATTAGE

COLOR SELECT
FIELD SELECTABLE

EFFICACY
UP TO 131 LM/W

01 ORDER INFORMATION

SKU / MODEL	SIZE	WATTAGE	CCT	VOLTAGE
ECO-X-MTA4F236WSCSAUV	2 ft	18/25/36 W	3000/4000/5000 K	120-277
ECO-X-MTA4F260WSCSAUV	4 ft	36/50/60 W	3000/4000/5000 K	120-277

02 ELECTRICAL CHARACTERISTICS

SPECIFICATION	18/25/36 W	36/50/60 W
Size	2 ft	4 ft
Input Voltage	120–277 V AC, 50/60 Hz	
Wattage	18 / 25 / 36 W	36 / 50 / 60 W
Lumen Output	2,250 – 4,100 lm	4,300 – 7,000 lm
Color Temperature (CCT)	3000K / 4000K / 5000K (selectable)	
CRI	>80	
LED Driver	2 lightbars / 1 driver	2 lightbars / 1 driver
Operating Temperature	-25 to +45°C (-13 to +113°F)	

03 DIMENSIONS

MODEL	LENGTH	WIDTH	HEIGHT
ECO-X-MTA4F236WSCSAUV	19.7" / 500 mm	11" / 279 mm	1.1" / 28 mm
ECO-X-MTA4F260WSCSAUV	43.3" / 1100 mm	11" / 279 mm	1.1" / 28 mm

Linear extrusion · Dimensions ±0.2" · inches [mm]

04 SAFETY WARNING

⚠ READ BEFORE INSTALLATION

1. Installation must be performed by a qualified, licensed electrician in accordance with all applicable national and local electrical codes.