EcoLite™
Leader in LED Lighting

PULSAR SELECT SEMI WALL PACK
SPECIFICATION SHEET
ECO-J-WP09

Pulsar Select Semi Wall Pack LED Light III

ECO-J-WP09
120-277



KEY SPECS

POWER	COLOR	EFFICACY	OPTICS
60–120W	**3CCT**	**Up to 150lm/W**	**IV**
Field-selectable output	3000 / 4000 / 5000 K	System efficacy	NEMA distribution

Pulsar Select Semi Wall Pack delivers field-selectable wattage and color temperature for pathway, entryway, and perimeter lighting. The die-cast aluminum housing features a dark bronze thermoset powder-coat finish and a high-UV polycarbonate lens for uniform distribution. A Sosen 0-10V dimmable driver accepts 120-277 V universal input, and an integral dusk-to-dawn photocell automates operation. The IP65-rated enclosure hinges open at the J-box for easy wall mounting and service, and the fixture ships UL Listed and DLC Premium qualified — backed by EcoLite's 10-year non-prorated warranty.

- Pathway lighting
- Building entryways
- Perimeter & security lighting
- Wall-mounted exterior lighting

FEATURES

01 Field-selectable wattage: 60 / 90 / 100 / 120 W
02 Field-selectable CCT: 3000 / 4000 / 5000 K
03 Integral dusk-to-dawn photocell
04 Die-cast aluminum housing with bronze powder-coat finish
05 Sosen 0-10V dimmable driver
06 IP65 wet-location rated

UL · DLC LISTED PREMIUM · THE LED INDUSTRY'S BEST 10 Year Non-Prorated WARRANTY

POWER SELECT
MULTI-WATTAGE

COLOR SELECT
FIELD SELECTABLE

IP65
INGRESS
PROTECTED

01 ORDER INFORMATION

SKU / MODEL	WATTAGE	CCT	VOLTAGE
ECO-J-WP09-120W-S4W3C-PC	60/90/100/120 W	3000/4000/5000 K	120-277

02 ELECTRICAL CHARACTERISTICS

SPECIFICATION	60/90/100/120 W
Wattage	60 / 90 / 100 / 120 W (switchable)
Lumen Output	9,000 – 18,000 lm
Color Temperature (CCT)	3000 / 4000 / 5000 K (switchable)
Efficacy (lm/W)	Up to 150 lm/W
CRI	≥80
Input Voltage	120–277 VAC, 50/60 Hz
LED Driver	Sosen brand, 0-10V dimmable
Beam Angle	Type IV
Operating Temperature	-40 to +45°C
Photocell	Integral dusk-to-dawn
Ingress Protection (IP)	IP65

03 ACCESSORIES & MOUNTING



GLARE SHIELD

Optional add-on



WIRE GUARD

Optional add-on



EMERGENCY BATTERY BACKUP, 15W

ECO-BLDCM15N



MICROWAVE MOTION SENSOR

ECO-ANT5ZT

04 DIMENSIONS

MODEL	LENGTH	WIDTH	HEIGHT	WEIGHT
ECO-J-WP09-120W-S4W3C-PC	15” / 381 mm	11.8” / 300 mm	7.5” / 190 mm	9.1 lb

Rectangular footprint · Dimensions ±0.2" · inches [mm]

05 SAFETY WARNING

⚠ READ BEFORE INSTALLATION

1 Installation must be performed by a qualified, licensed electrician in accordance with all applicable national and local electrical codes.