EcoLite™
Leader in LED Lighting

VECTOR FULL CUTOFF WALL PACK
SPECIFICATION SHEET
ECO-J-WP11F

Vector Full Cutoff Wall Pack LED Light III

ECO-J-WP11F
120-277



KEY SPECS

POWER	COLOR	EFFICACY	VOLTAGE
60–120W	3CCT	160lm/W	120-277V
Field-selectable output	3000 / 4000 / 5000 K	System efficacy	Input voltage

Vector Full Cutoff Wall Pack is a rugged full-cutoff outdoor luminaire built on a die-cast aluminum housing with an optical polycarbonate lens for durable, glare-controlled illumination. Its Type III distribution and >80 CRI LED source deliver uniform, wide-area coverage across walkways, entries, and building perimeters. Field-selectable wattage and CCT run on a 120–277 V input with 0-10V dimming, 6 kV surge protection, and an integrated dusk-to-dawn photocell. The IP65-rated fixture wall-mounts with five 1/2" knockouts and supports an optional microwave motion sensor. UL-listed and DLC Premium for rebate eligibility, backed by EcoLite's 10-year non-prorated warranty.

- Factory & warehouse lighting
- Walkways & hallways
- Outdoor commercial
- Outdoor residential

FEATURES

01 Field-selectable wattage 60/90/100/120 W
02 Field-selectable CCT 3000/4000/5000K
03 Type III full-cutoff distribution
04 Integrated dusk-to-dawn photocell
05 6 kV surge protection
06 IP65 wet-location rating

c UL us LISTED
DLC LISTED PREMIUM
10 Year Non-Prorated WARRANTY
IP65 INGRESS PROTECTED
POWER SELECT MULTI-WATTAGE
COLOR SELECT FIELD SELECTABLE

01 ORDER INFORMATION

SKU / MODEL	WATTAGE	CCT	VOLTAGE
ECO-J-WP11F-120W-S4W3C-PC	60/90/100/120 W	3000/4000/5000 K	120-277

02 ELECTRICAL CHARACTERISTICS

SPECIFICATION	60/90/100/120 W
Input Voltage	120–277 V
Wattage	60 / 90 / 100 / 120 W
Lumen Output	19,200 lm
Efficacy (lm/W)	Up to 160 lm/W
Color Temperature (CCT)	3000K / 4000K / 5000K
CRI	>80
Dimming	0-10V
Surge Protection	6 kV
Operating Temperature	-40 to +50°C

03 ACCESSORIES & MOUNTING



EMERGENCY BATTERY BACKUP 18W

ECO-LS-EMWC18W

04 DIMENSIONS

MODEL	LENGTH	WIDTH	HEIGHT	WEIGHT
ECO-J-WP11F-120W-S4W3C-PC	14.48” / 368 mm	9.25” / 235 mm	6.44” / 164 mm	5.94 lb

Rectangular footprint · Dimensions ±0.2" · inches [mm]

05 SAFETY WARNING

⚠ READ BEFORE INSTALLATION

1 Installation must be performed by a qualified, licensed electrician in accordance with all applicable national and local electrical codes.